
bandersnatch Documentation

Release 4.1.0.dev2

PyPA

Jul 30, 2020

CONTENTS

1 Installation	3
1.1 pip	3
2 Mirror configuration	5
2.1 directory	5
2.2 json	5
2.3 master	6
2.4 timeout	6
2.5 global-timeout	6
2.6 workers	6
2.7 hash-index	7
2.7.1 Apache rewrite rules when using hash-index	7
2.7.2 NGINX rewrite rules when using hash-index	7
2.8 stop-on-error	7
2.9 log-config	7
2.10 root_uri	8
2.11 diff-file	8
2.12 diff-append-epoch	8
3 Mirror filtering	9
3.1 Plugins Enabling	9
3.2 blacklist / whitelist filtering settings	9
3.3 packages	10
3.4 Metadata Filtering	10
3.4.1 Project Regex Matching	10
3.4.2 Release File Regex Matching	11
3.5 Prerelease filtering	11
3.6 Regex filtering	11
3.7 Platform-specific binaries filtering	12
3.8 Keep only latest releases	12
4 Contributing	13
4.1 Code of Conduct	13
4.2 Getting Started	13
4.2.1 Pre Install	13
4.2.2 Development venv	13
4.3 Running Bandersnatch	16
4.4 Running Unit Tests	16
4.5 Making a release	18

5	bandersnatch	19
5.1	bandersnatch package	19
5.1.1	Package contents	19
5.1.2	Submodules	19
5.1.3	bandersnatch.configuration module	19
5.1.4	bandersnatch.delete module	20
5.1.5	bandersnatch.filter module	20
5.1.6	bandersnatch.log module	22
5.1.7	bandersnatch.main module	22
5.1.8	bandersnatch.master module	22
5.1.9	bandersnatch.mirror module	23
5.1.10	bandersnatch.package module	24
5.1.11	bandersnatch.storage module	25
5.1.12	bandersnatch.utils module	27
5.1.13	bandersnatch.verify module	28
5.2	bandersnatch_filter_plugins package	28
5.2.1	Package contents	28
5.2.2	Submodules	28
5.2.3	bandersnatch_filter_plugins.blacklist_name module	28
5.2.4	bandersnatch_filter_plugins.filename_name module	29
5.2.5	bandersnatch_filter_plugins.latest_name module	29
5.2.6	bandersnatch_filter_plugins.metadata_filter module	30
5.2.7	bandersnatch_filter_plugins.prerelease_name module	32
5.2.8	bandersnatch_filter_plugins.regex_name module	33
5.2.9	bandersnatch_filter_plugins.whitelist_name module	33
5.3	bandersnatch_storage_plugins package	34
5.3.1	Package contents	34
5.3.2	Submodules	34
5.3.3	bandersnatch_storage_plugins.filesystem module	34
5.3.4	bandersnatch_storage_plugins.swift module	36
	Python Module Index	41
	Index	43

bandersnatch is a PyPI mirror client according to *PEP 381* <http://www.python.org/dev/peps/pep-0381/>.

Bandersnatch hits the XMLRPC API of pypi.org to get all packages with serial or packages since the last run's serial. bandersnatch then uses the JSON API of PyPI to get shasums and release file paths to download and workout where to layout the package files on a POSIX file system.

As of 4.0 bandersnatch: - Is fully asyncio based (mainly via aiohttp) - Only stores PEP503 normalized package names for the /simple API - Only stores JSON in normalized package name path too

Contents:

CHAPTER
ONE

INSTALLATION

The following instructions will place the bandersnatch executable in a virtualenv under bandersnatch/bin/bandersnatch.

- bandersnatch **requires** >= Python 3.6

1.1 pip

This installs the latest stable, released version.

(>= 3.6.1 required)

```
$ python3.6 -m venv bandersnatch
$ bandersnatch/bin/pip install bandersnatch
$ bandersnatch/bin/bandersnatch --help
```

CHAPTER
TWO

MIRROR CONFIGURATION

The mirror configuration settings are in a configuration section of the configuration file named **[mirror]**.

This section contains settings to specify how the mirroring software should operate.

2.1 directory

The mirror directory setting is a string that specifies the directory to store the mirror files.

The directory used must meet the following requirements:

- The filesystem must be case-sensitive filesystem.
- The filesystem must support large numbers of sub-directories.
- The filesystem must support large numbers of files (inodes)

Example:

```
[mirror]
directory = /srv/pypi
```

2.2 json

The mirror json setting is a boolean (true/false) setting that indicates that the json packaging metadata should be mirrored in addition to the packages.

Example:

```
[mirror]
json = false
```

2.3 master

The master setting is a string containing a url of the server which will be mirrored.

The master url string must use https: protocol.

The default value is: https://pypi.org

Example:

```
[mirror]
master = https://pypi.org
```

2.4 timeout

The timeout value is an integer that indicates the maximum number of seconds for web requests.

The default value for this setting is 10 seconds.

Example:

```
[mirror]
timeout = 10
```

2.5 global-timeout

The global-timeout value is an integer that indicates the maximum runtime of individual aiohttp coroutines.

The default value for this setting is 18000 seconds, or 5 hours.

Example:

```
[mirror]
global-timeout = 18000
```

2.6 workers

The workers value is an integer from from 1-10 that indicates the number of concurrent downloads.

The default value is 3.

Recommendations for the workers setting:

- leave the default of 3 to avoid overloading the pypi master
- official servers located in data centers could run 10 workers
- anything beyond 10 is probably unreasonable and is not allowed.

2.7 hash-index

The hash-index is a boolean (true/false) to determine if package hashing should be used.

The Recommended setting: the default of false for full pip/pypi compatibility.

Warning: Package index directory hashing is incompatible with pip, and so this should only be used in an environment where it is behind an application that can translate URIs to filesystem locations.

2.7.1 Apache rewrite rules when using hash-index

When using this setting with an apache server. The apache server will need the following rewrite rules:

```
RewriteRule ^([^\/])([^\/*]*/$ /mirror/pypi/web/simple/$1/$1$2/
RewriteRule ^([^\/])([^\/*]*/([^\/*]+)$ /mirror/pypi/web/simple/$1/$1$2/$3
```

2.7.2 NGINX rewrite rules when using hash-index

When using this setting with an nginx server. The nginx server will need the following rewrite rules:

```
rewrite ^/simple/([^\/])([^\/*]*/$ /simple/$1/$1$2/ last;
rewrite ^/simple/([^\/])([^\/*]*/([^\/*]+)$ /simple/$1/$1$2/$3 last;
```

2.8 stop-on-error

The stop-on-error setting is a boolean (true/false) setting that indicates if bandersnatch should stop immediately if it encounters an error.

If this setting is false it will not stop when an error is encountered but it will not mark the sync as successful when the sync is complete.

```
[mirror]
stop-on-error = false
```

2.9 log-config

The log-config setting is a string containing the filename of a python logging configuration file.

Example:

```
[mirror]
log-config = /etc/bandersnatch-log.conf
```

2.10 root_uri

The root_uri is a string containing a uri which is the root added to relative links.

Note: This is generally not necessary, but was added for the official internal PyPI mirror, which requires serving packages from <https://files.pythonhosted.org>

Example:

```
[mirror]
root_uri = https://example.com
```

2.11 diff-file

The diff file is a string containing the filename to log the files that were downloaded during the mirror. This file can then be used to synchronize external disks or send the files through some other mechanism to offline systems. You can then sync the list of files to an attached drive or ssh destination such as a diode:

```
rsync -av --files-from=/srv/pypi/mirrored-files / /mnt/usb/
```

You can also use this file list as an input to 7zip to create split archives for transfers, allowing you to size the files as you needed:

```
7za a -i@"/srv/pypi/mirrored-files" -spf -v100m path_to_new_zip.7z
```

Example:

```
[mirror]
diff-file = /srv/pypi/mirrored-files
```

2.12 diff-append-epoch

The diff append epoch is a boolean (true/false) setting that indicates if the diff-file should be appended with the current epoch time. This can be used to track diffs over time so the diff file doesn't get clobbered each run. It is only used when diff-file is used.

Example:

```
[mirror]
diff-append-epoch = true
```

MIRROR FILTERING

The mirror filter configuration settings are in the same configuration file as the mirror settings. There are different configuration sections for the different plugin types.

Filtering Plugin pacakage lists need to use the **Raw PyPI Name** (non PEP503 normalized) in order to get filtered.

E.g. to Blacklist [ACMPlus](#) you'd need to use that *exact* casing in `bandersnatch.conf`

- A PR would be welcome fixing the normalization but it's an invasive PR

3.1 Plugins Enabling

The plugins setting is a list of plugins to enable.

Example (enable all installed filter plugins):

- *Explicitly* enabling plugins is now **mandatory** for *activating plugins*
- They will *do nothing* without activation

Also, enabling will get plugin's defaults if not configured in their respective sections.

```
[plugins]
enabled = all
```

Example (only enable specific plugins):

```
[plugins]
enabled =
    blacklist_project
    whitelist_project
    ...
```

3.2 blacklist / whitelist filtering settings

The blacklist / whitelist settings are in configuration sections named **[blacklist]** and **[whitelist]** these section provides settings to indicate packages, projects and releases that should / should not be mirrored from PyPI.

This is useful to avoid syncing broken or malicious packages.

3.3 packages

The packages setting is a list of python pep440 version specifier of packages to not be mirrored. Enable version specifier filtering for whitelist and blacklist packages through enabling the ‘blacklist_release’ and ‘allowlist_release’ plugins, respectively.

Any packages matching the version specifier for blacklist packages will not be downloaded. Any packages not matching the version specifier for whitelist packages will not be downloaded.

Example:

```
[plugins]
enabled =
    blacklist_project
    blacklist_release
    whitelist_project
    allowlist_release

[blacklist]
packages =
    example1
    example2>=1.4.2,<1.9,!>=1.5.*,!>=1.6.*

[whitelist]
packages =
    black==18.5
    ptr
```

3.4 Metadata Filtering

Packages and release files may be selected by filtering on specific metadata value.

General form of configuration entries is:

```
[filter_some_metadata]
tag:tag:path.to.object =
    matcha
    matchb
```

3.4.1 Project Regex Matching

Filter projects to be synced based on regex matches against their raw metadata entries straight from parsed downloaded json.

Example:

```
[regex_project_metadata]
not-null:info.classifiers =
    .*Programming Language :: Python :: 2.*
```

Valid tags are all,any,none,match-null,not-null, with default of any:match-null

All metadata provided by json is available, including info, last_serial, releases, etc. headings.

3.4.2 Release File Regex Matching

Filter release files to be downloaded for projects based on regex matches against the stored metadata entries for each release file.

Example:

```
[regex_release_file_metadata]
any:release_file.packagetype =
    sdist
    bdist_wheel
```

Valid tags are the same as for projects.

Metadata available to match consists of `info`, `release`, and `release_file` top level structures, with `info` containing the package-wide information, `release` containing the version of the release and `release_file` the metadata for an individual file for that release.

3.5 Prerelease filtering

Bandersnatch includes a plugin to filter our pre-releases of packages. To enable this plugin simply add `prerelease_release` to the enabled plugins list.

```
[plugins]
enabled =
    prerelease_release
```

3.6 Regex filtering

Advanced users who would like finer control over which packages and releases to filter can use the regex Bandersnatch plugin.

This plugin allows arbitrary regular expressions to be defined in the configuration, any package name or release version that matches will *not* be downloaded.

The plugin can be activated for packages and releases separately. For example to activate the project regex filter simply add it to the configuration as before:

```
[plugins]
enabled =
    regex_project
```

If you'd like to filter releases using the regex filter use `regex_release` instead.

The regex plugin requires an extra section in the config to define the actual patterns to used for filtering:

```
[filter_regex]
packages =
    .+-evil$
releases =
    .+alpha\d$
```

Note the same `filter_regex` section may include a `packages` and a `releases` entry with any number of regular expressions.

3.7 Platform-specific binaries filtering

This filter allows advanced users not interesting in Windows/macOS/Linux specific binaries to not mirror the corresponding files.

```
[plugins]
enabled =
    exclude_platform
[blacklist]
platforms =
    windows
```

Available platforms are: windows macos freebsd linux.

3.8 Keep only latest releases

You can also keep only the latest releases based on greatest [Version](#) numbers.

```
[plugins]
enabled =
    latest_release

[latest_release]
keep = 3
```

By default, the plugin does not filter out any release. You have to add the `keep` setting.

You should be aware that it can break requirements.

CONTRIBUTING

So you want to help out? **Awesome**. Go you!

4.1 Code of Conduct

Everyone interacting in the bandersnatch project's codebases, issue trackers, chat rooms, and mailing lists is expected to follow the [PSF Code of Conduct](#).

4.2 Getting Started

Bandersnatch is developed using the [GitHub Flow](#)

4.2.1 Pre Install

Please make sure your system has the following:

- Python 3.6.1 or greater

4.2.2 Development venv

One way to develop and install all the dependencies of bandersnatch is to use a venv.

- First create one and upgrade pip

```
python3.6 -m venv /path/to/venv
/path/to/venv/bin/pip install --upgrade pip
```

For example:

```
$ python3.6 -m venv bandersnatchvenv
$ bandersnatchvenv/bin/pip install --upgrade pip
Collecting pip
  Using cached https://files.pythonhosted.org/packages/0f/74/
  ↳ecd13431bcc456ed390b44c8a6e917c1820365cbebc6a8974d1cd045ab4/pip-10.0.1-py3-
  ↳none-any.whl
Installing collected packages: pip
  Found existing installation: pip 9.0.3
    Uninstalling pip-9.0.3:
```

(continues on next page)

(continued from previous page)

```
Successfully uninstalled pip-9.0.3
Successfully installed pip-10.0.1
```

- Then install the dependencies to the venv:

```
/path/to/venv/bin/pip install -r requirements.txt -r test-requirements.txt
```

For example:

```
$ bandersnatchvenv/bin/pip install -r requirements.txt -r test-requirements.txt
Collecting six==1.10.0 (from -r requirements.txt (line 2))
  Downloading https://files.pythonhosted.org/packages/c8/0a/
  ↳b6723e1bc4c516cb687841499455a8505b44607ab535be01091c0f24f079/six-1.10.0-py2.py3-
  ↳none-any.whl
Collecting pyparsing==2.1.10 (from -r requirements.txt (line 3))
  Downloading https://files.pythonhosted.org/packages/2b/f7/
  ↳e5a178fc3ea4118a0edce2a8d51fc14e680c745cf4162e4285b437c43c94/pyparsing-2.1.10-py2.
  ↳py3-none-any.whl (56kB)
    100% | | 61kB 2.3MB/s
Collecting python-dateutil==2.6.0 (from -r requirements.txt (line 4))
  Downloading https://files.pythonhosted.org/packages/40/8b/
  ↳275015d7a9ec293cf1bbf55433258fbc9d0711890a7f6dc538bac7b86bce/python_dateutil-2.6.0-
  ↳py2.py3-none-any.whl (194kB)
    100% | | 194kB 1.3MB/s
Collecting packaging==16.8 (from -r requirements.txt (line 5))
  Downloading https://files.pythonhosted.org/packages/87/1b/
  ↳c39b7c65b5612812b83d6cab7ef2885eac9f6beb0b7b8a7071a186aea3b1/packaging-16.8-py2.py3-
  ↳none-any.whl
Collecting requests==2.12.4 (from -r requirements.txt (line 6))
  Downloading https://files.pythonhosted.org/packages/ed/9e/
  ↳60cc074968c095f728f0d8d28370e8d396fa60afb7582735563cccf223dd/requests-2.12.4-py2.
  ↳py3-none-any.whl (576kB)
    100% | | 583kB 3.2MB/s
Collecting xmlrpc==0.3.1 (from -r requirements.txt (line 7))
Collecting bandersnatch==2.1.3 (from -r requirements.txt (line 8))
  Downloading https://files.pythonhosted.org/packages/25/41/
  ↳9082fcfb20ff536f990e538957eed7474d78b9dcecd018530684ae058995/bandersnatch-2.1.3-py3-
  ↳none-any.whl
Collecting flake8 (from -r test-requirements.txt (line 1))
  Downloading https://files.pythonhosted.org/packages/b9/dc/
  ↳14e9d94c770b8c4ef584e906c7583e74864786a58d47de101f2767d50c0b/flake8-3.5.0-py2.py3-
  ↳none-any.whl (69kB)
    100% | | 71kB 4.8MB/s
Collecting pep8 (from -r test-requirements.txt (line 2))
  Downloading https://files.pythonhosted.org/packages/42/3f/
  ↳669429ce58de2c22d8d2c542752e137ec4b9885fff398d3eceb1a7f5acb4/pep8-1.7.1-py2.py3-
  ↳none-any.whl (41kB)
    100% | | 51kB 9.6MB/s
Collecting pytest (from -r test-requirements.txt (line 3))
  Downloading https://files.pythonhosted.org/packages/76/52/
  ↳fc48d02492d9e6070cb672d9133382e83084f567f88eff1c27bd2c6c27a8/pytest-3.5.1-py2.py3-
  ↳none-any.whl (192kB)
    100% | | 194kB 2.8MB/s
Collecting pytest-codecheckers (from -r test-requirements.txt (line 4))
  Downloading https://files.pythonhosted.org/packages/53/09/
  ↳263669db13955496e77017f389693c1e1dd77d98fd4afdf51b133162e858f/pytest-codecheckers-0.
  ↳2.tar.gz
```

(continues on next page)

(continued from previous page)

```

Collecting pytest-cov (from -r test-requirements.txt (line 5))
    Downloading https://files.pythonhosted.org/packages/30/7d/
    ↳ 7f6a78ae44a1248ee28cc777586c18b28a1df903470e5d34a6e25712b8aa/pytest_cov-2.5.1-py2.
    ↳ py3-none-any.whl
Collecting pytest-timeout (from -r test-requirements.txt (line 6))
    Downloading https://files.pythonhosted.org/packages/69/7f/
    ↳ 33a67c2494c6c337daca935192b7de09d30b54e568c981ed0681380393c4/pytest_timeout-1.2.1-
    ↳ py2.py3-none-any.whl
Collecting pytest-cache (from -r test-requirements.txt (line 7))
    Downloading https://files.pythonhosted.org/packages/d1/15/
    ↳ 082fd0428aab33d2bafa014f3beb241830427ba803a8912a5aaeaf3a5663/pytest_cache-1.0.tar.gz
Requirement already satisfied: setuptools in /private/tmp/bandersnatchvenv/lib/
    ↳ python3.6/site-packages (from -r test-requirements.txt (line 8)) (39.0.1)
Collecting tox (from -r test-requirements.txt (line 9))
    Downloading https://files.pythonhosted.org/packages/e6/41/
    ↳ 4dcfd713282bf3213b0384320fa8841e4db032ddcb80bc08a540159d42a8/tox-3.0.0-py2.py3-none-
    ↳ any.whl (60kB)
        100% || 61kB 2.2MB/s
Collecting pycodestyle<2.4.0,>=2.0.0 (from flake8->-r test-requirements.txt (line 1))
    Downloading https://files.pythonhosted.org/packages/e4/81/
    ↳ 78fe51eb4038d1388b7217dd63770b0f428370207125047312886c923b26/pycodestyle-2.3.1-py2.
    ↳ py3-none-any.whl (45kB)
        100% || 51kB 4.4MB/s
Collecting mccabe<0.7.0,>=0.6.0 (from flake8->-r test-requirements.txt (line 1))
    Downloading https://files.pythonhosted.org/packages/87/89/
    ↳ 479dc97e18549e21354893e4ee4ef36db1d237534982482c3681ee6e7b57/mccabe-0.6.1-py2.py3-
    ↳ none-any.whl
Collecting pyflakes<1.7.0,>=1.5.0 (from flake8->-r test-requirements.txt (line 1))
    Downloading https://files.pythonhosted.org/packages/d7/40/
    ↳ 733bcc64da3161ae4122c11e88269f276358ca29335468005cb0ee538665/pyflakes-1.6.0-py2.py3-
    ↳ none-any.whl (227kB)
        100% || 235kB 2.6MB/s
Collecting py>=1.5.0 (from pytest->-r test-requirements.txt (line 3))
    Downloading https://files.pythonhosted.org/packages/67/a5/
    ↳ f77982214dd4c8fd104b066f249adea2c49e25e8703d284382eb5e9ab35a/py-1.5.3-py2.py3-none-
    ↳ any.whl (84kB)
        100% || 92kB 3.8MB/s
Collecting pluggy<0.7,>=0.5 (from pytest->-r test-requirements.txt (line 3))
    Downloading https://files.pythonhosted.org/packages/ba/65/
    ↳ ded3bc40bbf8d887f262f150fbe1ae6637765b5c9534bd55690ed2c0b0f7/pluggy-0.6.0-py3-none-
    ↳ any.whl
Collecting more-itertools>=4.0.0 (from pytest->-r test-requirements.txt (line 3))
    Downloading https://files.pythonhosted.org/packages/7a/46/
    ↳ 886917c6a4ce49dd3fff250c01c5abac5390d57992751384fe61befc4877/more_itertools-4.1.0-
    ↳ py3-none-any.whl (47kB)
        100% || 51kB 3.9MB/s
Collecting attrs>=17.4.0 (from pytest->-r test-requirements.txt (line 3))
    Downloading https://files.pythonhosted.org/packages/41/59/
    ↳ cedf87e91ed541be7957c501a92102f9cc6363c623a7666d69d51c78ac5b/attrs-18.1.0-py2.py3-
    ↳ none-any.whl
Collecting coverage>=3.7.1 (from pytest-cov->-r test-requirements.txt (line 5))
    Downloading https://files.pythonhosted.org/packages/a3/7e/
    ↳ c94c21d643bfe7017615994df7b52292a33c8dcf36a6f694af110594edba/coverage-4.5.1-cp36-
    ↳ cp36m-macosx_10_12_x86_64.whl (178kB)
        100% || 184kB 3.3MB/s
Collecting execnet>=1.1.dev1 (from pytest-cache->-r test-requirements.txt (line 7))
    Downloading https://files.pythonhosted.org/packages/f9/76/
    ↳ 3343e69a2a1602052f587898934e5fea395d22310d39c07955596597227c/execnet-1 (continues on nextpage)
    ↳ none-any.whl

```

(continued from previous page)

```
Collecting virtualenv>=1.11.2 (from tox->-r test-requirements.txt (line 9))
  Downloading https://files.pythonhosted.org/packages/ed/ea/
    ↪e20b5cbebf45d3096e8138ab74eda139595d827677f38e9dd543e6015bdf/virtualenv-15.2.0-py2.
    ↪py3-none-any.whl (2.6MB)
      100% | 2.6MB 3.3MB/s
Collecting apipkg>=1.4 (from execnet>=1.1.dev1->pytest-cache->-r test-requirements.
  ↪txt (line 7))
  Downloading https://files.pythonhosted.org/packages/94/72/
    ↪fd4f2e46ce7b0d388191c819ef691c8195fab09602bbf1a2f92aa5351444/apipkg-1.4-py2.py3-
    ↪none-any.whl
Installing collected packages: six, pyparsing, python-dateutil, packaging, requests,_
  ↪xmlrpc2, bandersnatch, pycodestyle, mccabe, pyflakes, flake8, pep8, py, pluggy,_
  ↪more-itertools, attrs, pytest, pytest-codecheckers, coverage, pytest-cov, pytest-
  ↪timeout, apipkg, execnet, pytest-cache, virtualenv, tox
  Running setup.py install for pytest-codecheckers ... done
  Running setup.py install for pytest-cache ... done
Successfully installed apipkg-1.4 attrs-18.1.0 bandersnatch-2.1.3 coverage-4.5.1_
  ↪execnet-1.5.0 flake8-3.5.0 mccabe-0.6.1 more-itertools-4.1.0 packaging-16.8 pep8-1.
  ↪7.1 pluggy-0.6.0 py-1.5.3 pycodestyle-2.3.1 pyflakes-1.6.0 pyparsing-2.1.10 pytest-
  ↪3.5.1 pytest-cache-1.0 pytest-codecheckers-0.2 pytest-cov-2.5.1 pytest-timeout-1.2.
  ↪1 python-dateutil-2.6.0 requests-2.12.4 six-1.10.0 tox-3.0.0 virtualenv-15.2.0_
  ↪xmlrpc2-0.3.1
```

4.3 Running Bandersnatch

You will need to customize `src/bandersnatch/default.conf` and run via the following:

WARNING: Bandersnatch will go off and sync from pypi.org and use large amounts of disk space!

```
cd bandersnatch
/path/to/venv/bin/pip install --upgrade .
/path/to/venv/bin/bandersnatch -c src/bandersnatch/default.conf mirror
```

4.4 Running Unit Tests

We use tox to run tests. `tox.ini` has the options needed, so running tests is very easy.

```
cd bandersnatch
/path/to/venv/bin/tox [-vv]
```

For example:

```
$ tox
GLOB sdist-make: /Users/dhubbard/PycharmProjects/bandersnatch/setup.py
py36 create: /Users/dhubbard/PycharmProjects/bandersnatch/.tox/py36
py36 installdeps: -rtest-requirements.txt
py36 inst: /Users/dhubbard/PycharmProjects/bandersnatch/.tox/dist/bandersnatch-2.2.1.
  ↪zip
py36 installed: apipkg==1.4,attrs==18.1.0,bandersnatch==2.2.1,certifi==2018.4.16,
  ↪chardet==3.0.4,coverage==4.5.1,execnet==1.5.0,flake8==3.5.0,idna==2.6,mccabe==0.6.1,
  ↪more-itertools==4.1.0,packaging==17.1,pep8==1.7.1,pluggy==0.6.0,py==1.5.3,
  ↪pycodestyle==2.3.1,pyflakes==1.6.0,pyparsing==2.2.0,pytest==3.5.1,pytest-cache==1.0,
  ↪pytest-codecheckers==0.2,pytest-cov==2.5.1,pytest-timeout==1.2.1,python-dateutil==2.
  ↪7.3,requests==2.18.4,six==1.11.0,tox==3.0.0,urlib3==1.22,virtualenv==15.2.0,
  ↪xmlrpc2==0.3.1
```

(continues on next page)

(continued from previous page)

```

py36 runtests: PYTHONHASHSEED='42669967'
py36 runtests: commands[0] | pytest
=====
→ test session starts
→ =====
platform darwin -- Python 3.6.5, pytest-3.5.1, py-1.5.3, pluggy-0.6.0
rootdir: /Users/dhubbard/PycharmProjects/bandersnatch, inifile: pytest.ini
plugins: timeout-1.2.1, cov-2.5.1, codecheckers-0.2
timeout: 10.0s method: signal
collected 94 items

src/bandersnatch/__init__.py ..
→
→
→ [ 2%]
src/bandersnatch/buildout.py ..
→
→
→ [ 4%]
src/bandersnatch/log.py ..
→
→
→ [ 6%]
src/bandersnatch/main.py ..
→
→
→ [ 8%]
src/bandersnatch/master.py ..
→
→
→ [ 10%]
src/bandersnatch/mirror.py ..
→
→
→ [ 12%]
src/bandersnatch/package.py ..
→
→
→ [ 14%]
src/bandersnatch/release.py ..
→
→
→ [ 17%]
src/bandersnatch/utils.py ..
→
→
→ [ 19%]
src/bandersnatch/tests/conftest.py ..
→
→
→ [ 21%]
src/bandersnatch/tests/test_main.py .....
→
→
→ [ 28%]
src/bandersnatch/tests/test_master.py .....
→
→
→ [ 40%]

```

(continues on next page)

(continued from previous page)

```
src/bandersnatch/tests/test_mirror.py .....  
↳  
↳  
↳ [ 61%]  
src/bandersnatch/tests/test_package.py .....  
↳  
↳  
↳ [ 93%]  
src/bandersnatch/tests/test_utils.py ..  
↳  
↳  
↳ [100%]  
  
----- coverage: platform darwin, python 3.6.5-final-0 -----  
Coverage HTML written to dir htmlcov  
  
=====  
↳ 94 passed in 3.40 seconds  
=====  
  
↳ _____ summary _____  
↳  
↳  
py36: commands succeeded  
congratulations :)
```

You want to see:

```
py36: commands succeeded  
congratulations :)
```

4.5 Making a release

To be completed - @cooper has never used zc.buildout

BANDERSNATCH

5.1 bandersnatch package

5.1.1 Package contents

5.1.2 Submodules

5.1.3 bandersnatch.configuration module

Module containing classes to access the bandersnatch configuration file

```
class bandersnatch.configuration.BandersnatchConfig (*args: Any, **kwargs: Any)
Bases: object

load_configuration() → None
    Read the configuration from a configuration file

class bandersnatch.configuration.DeprecatedKey (old_section, old_key, new_section,
                                                new_key, deprecated_version)
Bases: tuple

property deprecated_version
    Alias for field number 4

property new_key
    Alias for field number 3

property new_section
    Alias for field number 2

property old_key
    Alias for field number 1

property old_section
    Alias for field number 0

class bandersnatch.configuration.SetConfigValues (json_save, root_uri, diff_file_path,
                                                 diff_append_epoch, digest_name,
                                                 storage_backend_name, cleanup)
Bases: tuple

property cleanup
    Alias for field number 6

property diff_append_epoch
    Alias for field number 3
```

```
property diff_file_path
    Alias for field number 2

property digest_name
    Alias for field number 4

property json_save
    Alias for field number 0

property root_uri
    Alias for field number 1

property storage_backend_name
    Alias for field number 5

class bandersnatch.configuration.Singleton
    Bases: type

bandersnatch.configuration.validate_config_values(config: configparser.ConfigParser, → bandersnatch.configuration.SetConfigValues
    parser: ConfigParser) → bandersnatch.configuration.SetConfigValues
```

5.1.4 bandersnatch.delete module

```
async bandersnatch.delete.delete_packages(config: configparser.ConfigParser, args: argparse.Namespace, master: bandersnatch.master.Master) → int
bandersnatch.delete.delete_path(blob_path: pathlib.Path, dry_run: bool = False) → int
```

5.1.5 bandersnatch.filter module

Blacklist management

```
class bandersnatch.filter.Filter(*args: Any, **kwargs: Any)
    Bases: object

Base Filter class

check_match(**kwargs: Any) → bool
    Check if the plugin matches based on the arguments provides.

    Returns True if the values match a filter rule, False otherwise

    Return type bool

filter(metadata: dict) → bool
    Check if the plugin matches based on the package's metadata.

    Returns True if the values match a filter rule, False otherwise

    Return type bool

initialize_plugin() → None
    Code to initialize the plugin

name = 'filter'

class bandersnatch.filter.FilterMetadataPlugin(*args: Any, **kwargs: Any)
    Bases: bandersnatch.filter.Filter

Plugin that blocks sync operations for an entire project based on info fields.
```

```
name = 'metadata_plugin'

class bandersnatch.filter.FilterProjectPlugin(*args: Any, **kwargs: Any)
    Bases: bandersnatch.filter.Filter
        Plugin that blocks sync operations for an entire project

    name = 'project_plugin'

class bandersnatch.filter.FilterReleaseFilePlugin(*args: Any, **kwargs: Any)
    Bases: bandersnatch.filter.Filter
        Plugin that modify the download of specific release or dist files

    name = 'release_file_plugin'

class bandersnatch.filter.FilterReleasePlugin(*args: Any, **kwargs: Any)
    Bases: bandersnatch.filter.Filter
        Plugin that modifies the download of specific releases or dist files

    name = 'release_plugin'

class bandersnatch.filter.LoadedFilters(load_all: bool = False)
    Bases: object
        A class to load all of the filters enabled

    ENTRYPPOINT_GROUPS = ['bandersnatch_filter_plugins.v2.project', 'bandersnatch_filter_pl...']

    filter_metadata_plugins() → List[bandersnatch.filter.Filter]
        Load and return the release filtering plugin objects

            Returns List of objects derived from the bandersnatch.filter.Filter class

            Return type list of bandersnatch.filter.Filter

    filter_project_plugins() → List[bandersnatch.filter.Filter]
        Load and return the release filtering plugin objects

            Returns List of objects derived from the bandersnatch.filter.Filter class

            Return type list of bandersnatch.filter.Filter

    filter_release_file_plugins() → List[bandersnatch.filter.Filter]
        Load and return the release file filtering plugin objects

            Returns List of objects derived from the bandersnatch.filter.Filter class

            Return type list of bandersnatch.filter.Filter

    filter_release_plugins() → List[bandersnatch.filter.Filter]
        Load and return the release filtering plugin objects

            Returns List of objects derived from the bandersnatch.filter.Filter class

            Return type list of bandersnatch.filter.Filter
```

5.1.6 bandersnatch.log module

```
bandersnatch.log.setup_logging(args: Any) → logging.StreamHandler
```

5.1.7 bandersnatch.main module

```
async bandersnatch.main.async_main(args: argparse.Namespace, config: configparser.ConfigParser) → int
```

```
bandersnatch.main.main(loop: Optional[asyncio.events.AbstractEventLoop] = None) → int
```

5.1.8 bandersnatch.master module

```
class bandersnatch.master.Master(url: str, timeout: float = 10.0, global_timeout: Optional[float] = 18000.0)
```

Bases: object

```
async all_packages() → Dict[str, int]
```

```
async changed_packages(last_serial: int) → Dict[str, int]
```

```
async check_for_stale_cache(path: str, required_serial: Optional[int], got_serial: Optional[int]) → None
```

```
get(path: str, required_serial: Optional[int], **kw: Any) → AsyncGenerator[aiohttp.client_reqrep.ClientResponse, None]
```

```
async get_package_metadata(package_name: str, serial: int = 0) → Any
```

```
async rpc(method_name: str, serial: int = 0) → Any
```

```
async url_fetch(url: str, file_path: pathlib.Path, executor: Optional[Union[concurrent.futures.ProcessPoolExecutor, concurrent.futures.thread.ThreadPoolExecutor]] = None, chunk_size: int = 65536) → None
```

property xmlrpc_url

```
exception bandersnatch.master.PackageNotFound(package_name: str)
```

Bases: Exception

We asked for package metadata from PyPI and it wasn't available

```
exception bandersnatch.master.StalePage
```

Bases: Exception

We got a page back from PyPI that doesn't meet our expected serial.

```
exception bandersnatch.master.XmlRpcError
```

Bases: aiohttp.client_exceptions.ClientError

Issue getting package listing from PyPI Repository

5.1.9 bandersnatch.mirror module

```
class bandersnatch.mirror.Mirror(homedir: pathlib.Path, master: bandersnatch.master.Master,
                                 storage_backend: Optional[str] = None, stop_on_error: bool
                                 = False, workers: int = 3, hash_index: bool = False,
                                 json_save: bool = False, digest_name: Optional[str]
                                 = None, root_uri: Optional[str] = None, keep_index_versions:
                                 int = 0, diff_file: Optional[Union[pathlib.Path, str]] =
                                 None, diff_append_epoch: bool = False, diff_full_path: Optional[Union[pathlib.Path, str]] = None, flock_timeout: int =
                                 1, diff_file_list: Optional[List] = None, *, cleanup: bool =
                                 False)

Bases: object

async cleanup_non_pep_503_paths(package: bandersnatch.package.Package) → None
    Before 4.0 we use to store backwards compatible named dirs for older pip This function checks for them
    and cleans them up

async determine_packages_to_sync() → None
    Update the self.packages_to_sync to contain packages that need to be synced.

diff_append_epoch = False

diff_file = None

diff_full_path = None

digest_name = 'sha256'

errors = False

find_package_indexes_in_dir(simple_dir: pathlib.Path) → List[str]
    Given a directory that contains simple packages indexes, return a sorted list of normalized package names.
    This presumes every directory within is a simple package index directory.

property generationfile

get_simple_dirs(simple_dir: pathlib.Path) → List[pathlib.Path]
    Return a list of simple index directories that should be searched for package indexes when compiling the
    main index page.

json_save = False

need_index_sync = True

now = None

async package_syncer(idx: int) → None
    packages_to_sync: Dict[str, Union[int, str]] = {}

record_finished_package(name: str) → None
    root_uri: Optional[str] = ''

property statusfile

stop_on_error = False

sync_index_page() → None
    async sync_packages() → None
    synced_serial = 0

async synchronize(specific_packages: Optional[List[str]] = None) → Dict[str, Set[str]]
```

```
target_serial = None
property todolist
property webdir
wrapup_successful_sync() → None

async bandersnatch.mirror.mirror(config: configparser.ConfigParser, specific_packages: Optional[List[str]] = None) → int
```

5.1.10 bandersnatch.package module

```
class bandersnatch.package.Package(name: str, serial: Union[int, str], mirror: Mirror)
Bases: object

async download_file(url: str, sha256sum: str, chunk_size: int = 65536) → Optional[pathlib.Path]
gen_data_requires_python(release: Dict) → str
generate_simple_page() → str
property info
property json_file
property json_pypi_symlink
property last_serial
property metadata
property release_files
property releases
save_json_metadata(package_info: Dict) → bool
    Take the JSON metadata we just fetched and save to disk
property simple_directory
async sync(filters: LoadedFilters, attempts: int = 3) → None
async sync_release_files() → None
    Purge + download files returning files removed + added
sync_simple_page() → None
async update_metadata(attempts: int = 3) → None

exception bandersnatch.package.StaleMetadata(package_name: str, attempts: int)
Bases: Exception

We attempted to retreive metadata from PyPI, but it was stale.
```

5.1.11 bandersnatch.storage module

Storage management

class `bandersnatch.storage.Storage(*args: Any, config: Optional[configparser.ConfigParser] = None, **kwargs: Any)`

Bases: `object`

Base Storage class

PATH_BACKEND

alias of `pathlib.Path`

static canonicalize_package(name: str) → str

compare_files(file1: Union[pathlib.Path, str], file2: Union[pathlib.Path, str]) → bool

Compare two files and determine whether they contain the same data. Return True if they match

copy_file(source: Union[pathlib.Path, str], dest: Union[pathlib.Path, str]) → None

Copy a file from `source` to `dest`

delete(path: Union[pathlib.Path, str], dry_run: bool = False) → int

Delete the provided path.

delete_file(path: Union[pathlib.Path, str], dry_run: bool = False) → int

Delete the provided path, recursively if necessary.

property directory

exists(path: Union[pathlib.Path, str]) → bool

Check whether the provided path exists

find(root: Union[pathlib.Path, str], dirs: bool = True) → str

A test helper simulating ‘find’.

Iterates over directories and filenames, given as relative paths to the root.

get_flock_path() → Union[pathlib.Path, str]

get_hash(path: Union[pathlib.Path, str], function: str = 'sha256') → str

Get the sha256sum of a given `path`

get_json_paths(name: str) → Sequence[Union[pathlib.Path, str]]

get_lock(path: str) → filelock.BaseFileLock

Retrieve the appropriate `FileLock` backend for this storage plugin

Parameters `path (str)` – The path to use for locking

Returns A `FileLock` backend for obtaining locks

Return type `filelock.BaseFileLock`

hash_file(path: Union[pathlib.Path, str], function: str = 'sha256') → str

initialize_plugin() → None

Code to initialize the plugin

is_dir(path: Union[pathlib.Path, str]) → bool

Check whether the provided path is a directory.

is_file(path: Union[pathlib.Path, str]) → bool

Check whether the provided path is a file.

iter_dir(path: Union[pathlib.Path, str]) → Generator[Union[pathlib.Path, str], None, None]

Iterate over the path, returning the sub-paths

```
mkdir(path: Union[pathlib.Path, str], exist_ok: bool = False, parents: bool = False) → None
    Create the provided directory

name = 'storage'

open_file(path: Union[pathlib.Path, str], text: bool = True) → Generator[IO, None, None]
    Yield a file context to iterate over. If text is true, open the file with 'rb' mode specified.

read_file(path: Union[pathlib.Path, str], text: bool = True, encoding: str = 'utf-8', errors: Optional[str] = None) → Union[str, bytes]
    Yield a file context to iterate over. If text is true, open the file with 'rb' mode specified.

rewrite(filepath: Union[pathlib.Path, str], mode: str = 'w', **kw: Any) → Generator[IO, None, None]
    Rewrite an existing file atomically to avoid programs running in parallel to have race conditions while
    reading.

rmdir(path: Union[pathlib.Path, str], recurse: bool = False, force: bool = False, ignore_errors: bool
      = False, dry_run: bool = False) → int
    Remove the directory. If recurse is True, allow removing empty children. If force is true, remove contents
    destructively.

symlink(source: Union[pathlib.Path, str], dest: Union[pathlib.Path, str]) → None
    Create a symlink at dest that points back at source

update_safe(filename: Union[pathlib.Path, str], **kw: Any) → Generator[IO, None, None]
    Rewrite a file atomically.

    Clients are allowed to delete the tmpfile to signal that they don't want to have it updated.

write_file(path: Union[pathlib.Path, str], contents: Union[str, bytes]) → None
    Write data to the provided path. If contents is a string, the file will be opened and written in "r" + "utf-8"
    mode, if bytes are supplied it will be accessed using "rb" mode (i.e. binary write).

class bandersnatch.storage.StoragePlugin(*args: Any, config: Optional[configparser.ConfigParser] = None,
                                         **kwargs: Any)
Bases: bandersnatch.storage.Storage

    Plugin that provides a storage backend for bandersnatch

    name = 'storage_plugin'

bandersnatch.storage.load_storage_plugins(entrypoint_group: str, enabled_plugin: Optional[str] = None, config: Optional[configparser.ConfigParser] = None, clear_cache: bool = False) → Set[bandersnatch.storage.Storage]
Load all storage plugins that are registered with pkg_resources
```

Parameters

- **entrypoint_group** (*str*) – The entrypoint group name to load plugins from
- **enabled_plugin** (*str*) – The optional enabled storage plugin to search for
- **config** (*configparser.ConfigParser*) – The optional configparser instance to pass in
- **clear_cache** (*bool*) – Whether to clear the plugin cache

Returns A list of objects derived from the Storage class

Return type List of Storage

```
bandersnatch.storage.storage_backend_plugins(backend: Optional[str] = 'filesystem', config: Optional[configparser.ConfigParser] = None, clear_cache: bool = False) → Iterable[bandersnatch.storage.Storage]
```

Load and return the release filtering plugin objects

Parameters

- **backend** (*str*) – The optional enabled storage plugin to search for
- **config** (*configparser.ConfigParser*) – The optional configparser instance to pass in
- **clear_cache** (*bool*) – Whether to clear the plugin cache

Returns List of objects derived from the bandersnatch.storage.Storage class

Return type list of bandersnatch.storage.Storage

5.1.12 bandersnatch.utils module

```
bandersnatch.utils.bandersnatch_safe_name(name: str) → str
```

Convert an arbitrary string to a standard distribution name Any runs of non-alphanumeric/. characters are replaced with a single ‘-’.

- This was copied from *pkg_resources* (part of *setuptools*)

bandersnatch also lower cases the returned name

```
bandersnatch.utils.convert_url_to_path(url: str) → str
```

```
bandersnatch.utils.find(root: Union[pathlib.Path, str], dirs: bool = True) → str
```

A test helper simulating ‘find’.

Iterates over directories and filenames, given as relative paths to the root.

```
bandersnatch.utils.hash(path: pathlib.Path, function: str = 'sha256') → str
```

```
bandersnatch.utils.make_time_stamp() → str
```

Helper function that returns a timestamp suitable for use in a filename on any OS

```
bandersnatch.utils.recursive_find_files(files: Set[pathlib.Path], base_dir: pathlib.Path) → None
```

```
bandersnatch.utils.rewrite(filepath: Union[str, pathlib.Path], mode: str = 'w', **kw: Any) → Generator[IO, None, None]
```

Rewrite an existing file atomically to avoid programs running in parallel to have race conditions while reading.

```
bandersnatch.utils.unlink_parent_dir(path: pathlib.Path) → None
```

Remove a file and if the dir is empty remove it

```
bandersnatch.utils.user_agent() → str
```

5.1.13 bandersnatch.verify module

```
async bandersnatch.verify.delete_unowned_files(mirror_base:          path-
                                                lib.Path,           executor:      concurrent.futures.thread.ThreadPoolExecutor,
                                                all_package_files: List[pathlib.Path],
                                                dry_run: bool) → int

async bandersnatch.verify.get_latest_json(master:                  bandersnatch.master.Master,
                                            json_path:    pathlib.Path, config: configparser.ConfigParser,
                                            executor:     Optional[concurrent.futures.thread.ThreadPoolExecutor]
                                            = None, delete_removed_packages: bool =
                                            False) → None

async bandersnatch.verify.metadata_verify(config: configparser.ConfigParser, args: argparse.Namespace) → int
Crawl all saved JSON metadata or online to check we have all packages if delete - generate a diff of unowned files

async bandersnatch.verify.verify(master: bandersnatch.master.Master, config: configparser.ConfigParser, json_file: str, mirror_base_path: pathlib.Path, all_package_files: List[pathlib.Path], args: argparse.Namespace, executor: Optional[concurrent.futures.thread.ThreadPoolExecutor] = None, releases_key: str = 'releases') → None

async bandersnatch.verify.verify_producer(master: bandersnatch.master.Master, config: configparser.ConfigParser, all_package_files: List[pathlib.Path], mirror_base_path: pathlib.Path, json_files: List[str], args: argparse.Namespace, executor: Optional[concurrent.futures.thread.ThreadPoolExecutor] = None) → None
```

5.2 bandersnatch_filter_plugins package

5.2.1 Package contents

5.2.2 Submodules

5.2.3 bandersnatch_filter_plugins.blacklist_name module

```
class bandersnatch_filter_plugins.blacklist_name.BlacklistProject(*args: Any,
                                                               **kwargs: Any)
```

Bases: *bandersnatch.filter.FilterProjectPlugin*

blacklist_package_names: List[str] = []

check_match(kwargs: Any) → bool**

Check if the package name matches against a project that is blacklisted in the configuration.

Parameters **name** (*str*) – The normalized package name of the package/project to check against the blacklist.

Returns True if it matches, False otherwise.

Return type bool

filter(*metadata: Dict*) → bool
Check if the plugin matches based on the package's metadata.

Returns True if the values match a filter rule, False otherwise

Return type bool

initialize_plugin() → None
Initialize the plugin

name = 'blacklist_project'

class bandersnatch_filter_plugins.blacklist_name.**BlacklistRelease**(*args: Any,
**kwargs:
Any)
Bases: *bandersnatch.filter.FilterReleasePlugin*

blacklist_package_names: List[packaging.requirements.Requirement] = []

filter(*metadata: Dict*) → bool
Returns False if version fails the filter, i.e. matches a blocklist version specifier

initialize_plugin() → None
Initialize the plugin

name = 'blacklist_release'

5.2.4 bandersnatch_filter_plugins.filename_name module

class bandersnatch_filter_plugins.filename_name.**ExcludePlatformFilter**(*args:
Any,
**kwargs:
Any)
Bases: *bandersnatch.filter.FilterReleaseFilePlugin*

Filters releases based on regex patters defined by the user.

filter(*metadata: Dict*) → bool
Returns False if file matches any of the filename patterns

initialize_plugin() → None
Initialize the plugin reading patterns from the config.

name = 'exclude_platform'

5.2.5 bandersnatch_filter_plugins.latest_name module

class bandersnatch_filter_plugins.latest_name.**LatestReleaseFilter**(*args: Any,
**kwargs:
Any)
Bases: *bandersnatch.filter.FilterReleasePlugin*

Plugin to download only latest releases

filter(*metadata: Dict*) → bool
Returns False if version fails the filter, i.e. is not a latest/current release

initialize_plugin() → None
Initialize the plugin reading patterns from the config.

```
keep = 0
latest: Sequence[str] = []
name = 'latest_release'
```

5.2.6 bandersnatch_filter_plugins.metadata_filter module

```
class bandersnatch_filter_plugins.metadata_filter.RegexFilter(*args:      Any,
                                                               **kwargs: Any)
Bases: bandersnatch.filter.Filter
Plugin to download only packages having metadata matching at least one of the specified patterns.

filter(metadata: Dict) → bool
    Filter out all projects that don't match the specified metadata patterns.

initialize_plugin() → None
    Initialize the plugin reading patterns from the config.

initialized = False
match_patterns = 'any'
name = 'regex_filter'
nulls_match = True
patterns: Dict = {}

class bandersnatch_filter_plugins.metadata_filter.RegexProjectMetadataFilter(*args:
                                                               Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterMetadataPlugin, bandersnatch_filter_plugins.
metadata_filter.RegexFilter
Plugin to download only packages having metadata matching at least one of the specified patterns.

filter(metadata: Dict) → bool
    Check if the plugin matches based on the package's metadata.

    Returns True if the values match a filter rule, False otherwise

    Return type bool

initialize_plugin() → None
initialized = False
match_patterns = 'any'
name = 'regex_project_metadata'
nulls_match = True
patterns: Dict = {}

class bandersnatch_filter_plugins.metadata_filter.RegexReleaseFileMetadataFilter(*args:
                                                               Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterReleaseFilePlugin, bandersnatch_filter_plugins.
metadata_filter.RegexFilter
```

Plugin to download only release files having metadata matching at least one of the specified patterns.

filter(*metadata*: Dict) → bool

Check if the plugin matches based on the package's metadata.

Returns True if the values match a filter rule, False otherwise

Return type bool

initialize_plugin() → None

initialized = False

match_patterns = 'any'

name = 'regex_release_file_metadata'

nulls_match = True

patterns: Dict = {}

```
class bandersnatch_filter_plugins.metadata_filter.VersionRangeFilter(*args:  
    Any,  
    **kwargs:  
    Any)
```

Bases: *bandersnatch.filter.Filter*

Plugin to download only items having metadata version ranges matching specified versions.

filter(*metadata*: Dict) → bool

Return False for input not having metadata entries matching the specified version specifier.

initialize_plugin() → None

Initialize the plugin reading version ranges from the config.

initialized = False

name = 'version_range_filter'

nulls_match = True

specifiers: Dict = {}

```
class bandersnatch_filter_plugins.metadata_filter.VersionRangeProjectMetadataFilter(*args:  
    Any,  
    **kwargs:  
    Any)
```

Bases: *bandersnatch.filter.FilterMetadataPlugin*, *bandersnatch_filter_plugins.metadata_filter.VersionRangeFilter*

Plugin to download only projects having metadata entries matching specified version ranges.

filter(*metadata*: dict) → bool

Check if the plugin matches based on the package's metadata.

Returns True if the values match a filter rule, False otherwise

Return type bool

initialize_plugin() → None

Code to initialize the plugin

initialized = False

name = 'version_range_project_metadata'

nulls_match = True

```
specifiers: Dict = {}

class bandersnatch_filter_plugins.metadata_filter.VersionRangeReleaseFileMetadataFilter(*args,
                                         Any,
                                         **kwargs,
                                         Any)

Bases: bandersnatch.filter.FilterReleaseFilePlugin, bandersnatch_filter_plugins.
metadata_filter.VersionRangeFilter

Plugin to download only release files having metadata entries matching specified version ranges.

filter(metadata: dict) → bool
    Check if the plugin matches based on the package's metadata.

    Returns True if the values match a filter rule, False otherwise

    Return type bool

initialize_plugin() → None
    Code to initialize the plugin

initialized = False

name = 'version_range_release_file_metadata'
nulls_match = True
specifiers: Dict = {}
```

5.2.7 bandersnatch_filter_plugins.prerelease_name module

```
class bandersnatch_filter_plugins.prerelease_name.PreReleaseFilter(*args,
                                                                    Any,
                                                                    **kwargs,
                                                                    Any)

Bases: bandersnatch.filter.FilterReleasePlugin

Filters releases considered pre-releases.

PRERELEASE_PATTERNS = ('.+rc\\d+$', '.+a(pha)?\\d+$', '.+b(eta)?\\d+$', '.+dev\\d+$')

filter(metadata: Dict) → bool
    Returns False if version fails the filter, i.e. follows a prerelease pattern

initialize_plugin() → None
    Initialize the plugin reading patterns from the config.

name = 'prerelease_release'

patterns: List[Pattern] = []
```

5.2.8 bandersnatch_filter_plugins.regex_name module

```
class bandersnatch_filter_plugins.regex_name.RegexProjectFilter(*args: Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterProjectPlugin
Filters projects based on regex patters defined by the user.

check_match(name: str) → bool
    Check if a release version matches any of the specified patterns.

    Parameters name (str) – Release name
    Returns True if it matches, False otherwise.
    Return type bool

filter(metadata: Dict) → bool
    Check if the plugin matches based on the package's metadata.

    Returns True if the values match a filter rule, False otherwise
    Return type bool

initialize_plugin() → None
    Initialize the plugin reading patterns from the config.

name = 'regex_project'
patterns: List[Pattern] = []

class bandersnatch_filter_plugins.regex_name.RegexReleaseFilter(*args: Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterReleasePlugin
Filters releases based on regex patters defined by the user.

filter(metadata: Dict) → bool
    Returns False if version fails the filter, i.e. follows a regex pattern

initialize_plugin() → None
    Initialize the plugin reading patterns from the config.

name = 'regex_release'
patterns: List[Pattern] = []
```

5.2.9 bandersnatch_filter_plugins.whitelist_name module

```
class bandersnatch_filter_plugins.whitelist_name.AllowlistRelease(*args: Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterReleasePlugin
allowlist_package_names: List[packaging.requirements.Requirement] = []
filter(metadata: Dict) → bool
    Returns False if version fails the filter, i.e. doesn't matches an allowlist version specifier

initialize_plugin() → None
    Initialize the plugin
```

```
name = 'allowlist_release'

class bandersnatch_filter_plugins.whitelist_name.WhitelistProject (*args: Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.filter.FilterProjectPlugin

check_match (**kwargs: Any) → bool
    Check if the package name matches against a project that is blacklisted in the configuration.

        Parameters name (str) – The normalized package name of the package/project to check
                    against the blacklist.

        Returns True if it matches, False otherwise.

        Return type bool

filter (metadata: Dict) → bool
    Check if the plugin matches based on the package's metadata.

        Returns True if the values match a filter rule, False otherwise

        Return type bool

initialize_plugin() → None
    Initialize the plugin

name = 'whitelist_project'
whitelist_package_names: List[str] = []
```

5.3 bandersnatch_storage_plugins package

5.3.1 Package contents

5.3.2 Submodules

5.3.3 bandersnatch_storage_plugins.filesystem module

```
class bandersnatch_storage_plugins.filesystem.FilesystemStorage (*args: Any,
                                                               **kwargs:
                                                               Any)
Bases: bandersnatch.storage.StoragePlugin

PATH_BACKEND
    alias of pathlib.Path

compare_files (file1: Union[pathlib.Path, str], file2: Union[pathlib.Path, str]) → bool
    Compare two files, returning true if they are the same and False if not.

copy_file (source: Union[pathlib.Path, str], dest: Union[pathlib.Path, str]) → None
    Copy a file from source to dest

delete_file (path: Union[pathlib.Path, str], dry_run: bool = False) → int
    Delete the provided path, recursively if necessary.

exists (path: Union[pathlib.Path, str]) → bool
    Check whether the provided path exists
```

find (*root*: Union[pathlib.Path, str], *dirs*: bool = True) → str
A test helper simulating ‘find’.
Iterates over directories and filenames, given as relative paths to the root.

get_hash (*path*: Union[pathlib.Path, str], *function*: str = ‘sha256’) → str
Get the sha256sum of a given **path**

get_lock (*path*: Optional[str] = None) → filelock.UnixFileLock
Retrieve the appropriate *FileLock* backend for this storage plugin

Parameters **path** (str) – The path to use for locking

Returns A *FileLock* backend for obtaining locks

Return type *SwiftFileLock*

is_dir (*path*: Union[pathlib.Path, str]) → bool
Check whether the provided path is a directory.

is_file (*path*: Union[pathlib.Path, str]) → bool
Check whether the provided path is a file.

mkdir (*path*: Union[pathlib.Path, str], *exist_ok*: bool = False, *parents*: bool = False) → None
Create the provided directory

name = ‘filesystem’

open_file (*path*: Union[pathlib.Path, str], *text*: bool = True, *encoding*: str = ‘utf-8’) → Generator[IO, None, None]
Yield a file context to iterate over. If *text* is true, open the file with ‘rb’ mode specified.

read_file (*path*: Union[pathlib.Path, str], *text*: bool = True, *encoding*: str = ‘utf-8’, *errors*: Optional[str] = None) → Union[str, bytes]
Return the contents of the requested file, either a bytestring or a unicode string depending on whether *text* is True

rewrite (*filepath*: Union[pathlib.Path, str], *mode*: str = ‘w’, **kw: Any) → Generator[IO, None, None]
Rewrite an existing file atomically to avoid programs running in parallel to have race conditions while reading.

rmdir (*path*: Union[pathlib.Path, str], *recurse*: bool = False, *force*: bool = False, *ignore_errors*: bool = False, *dry_run*: bool = False) → int
Remove the directory. If *recurse* is True, allow removing empty children. If *force* is true, remove contents destructively.

update_safe (*filename*: Union[pathlib.Path, str], **kw: Any) → Generator[IO, None, None]
Rewrite a file atomically.
Clients are allowed to delete the tmpfile to signal that they don’t want to have it updated.

walk (*root*: Union[pathlib.Path, str], *dirs*: bool = True) → List[pathlib.Path]

write_file (*path*: Union[pathlib.Path, str], *contents*: Union[str, bytes]) → None
Write data to the provided path. If **contents** is a string, the file will be opened and written in “r” + “utf-8” mode, if bytes are supplied it will be accessed using “rb” mode (i.e. binary write).

5.3.4 bandersnatch_storage_plugins.swift module

```
class bandersnatch_storage_plugins.swift.SwiftFileLock(lock_file: str, timeout: int = -1, backend: Optional[SwiftStorage] = None)
Bases: filelock.BaseFileLock

Simply watches the existence of the lock file.

property is_locked
    True, if the object holds the file lock.

    Changed in version 2.0.0: This was previously a method and is now a property.

property path_backend

class bandersnatch_storage_plugins.swift.SwiftPath(*args: Any)
Bases: pathlib.Path

BACKEND: 'SwiftStorage'

absolute() → bandersnatch_storage_plugins.swift.SwiftPath
    Return an absolute version of this path. This function works even if the path doesn't point to anything.

    No normalization is done, i.e. all '.' and '..' will be kept along. Use resolve() to get the canonical path to a file.

property backend

exists() → bool
    Whether this path exists.

is_dir() → bool
    Whether this path is a directory.

is_file() → bool
    Whether this path is a regular file (also True for symlinks pointing to regular files).

is_symlink() → bool
    Whether this path is a symbolic link.

iterdir(conn: Optional[swiftclient.client.Connection] = None, recurse: bool = False, include_swiftkeep: bool = False) → Generator[bandersnatch_storage_plugins.swift.SwiftPath, None, None]
    Iterate over the files in this directory. Does not yield any result for the special paths '.' and '..'.

mkdir(mode: int = 511, parents: bool = False, exist_ok: bool = False) → None
    Create a new directory at this given path.

read_bytes() → bytes
    Open the file in bytes mode, read it, and close the file.

read_text(encoding: Optional[str] = None, errors: Optional[str] = None) → str
    Open the file in text mode, read it, and close the file.

classmethod register_backend(backend: bandersnatch_storage_plugins.swift.SwiftStorage) → None
symlink_to(src: Union[pathlib.Path, str], target_is_directory: bool = False, src_container: Optional[str] = None, src_account: Optional[str] = None) → None
    Make this path a symlink pointing to the given path. Note the order of arguments (self, target) is the reverse of os.symlink's.
```

touch() → None
 Create this file with the given access mode, if it doesn't exist.

unlink(missing_ok: bool = False) → None
 Remove this file or link. If the path is a directory, use rmdir() instead.

write_bytes(contents: bytes, encoding: Optional[str] = 'utf-8', errors: Optional[str] = None) → int
 Open the file in bytes mode, write to it, and close the file.

write_text(contents: Optional[str], encoding: Optional[str] = 'utf-8', errors: Optional[str] = None)
 → int
 Open the file in text mode, write to it, and close the file.

class bandersnatch_storage_plugins.swift.SwiftStorage(*args: Any, config: Optional[configparser.ConfigParser] = None, **kwargs: Any)
 Bases: *bandersnatch.storage.StoragePlugin*

PATH_BACKEND
 alias of *SwiftPath*

compare_files(file1: Union[pathlib.Path, str], file2: Union[pathlib.Path, str]) → bool
 Compare two files, returning true if they are the same and False if not.

connection() → Generator[*swiftclient.client.Connection*, None, None]

copy_file(source: Union[pathlib.Path, str], dest: Union[pathlib.Path, str], dest_container: Optional[str] = None) → None
 Copy a file from **source** to **dest**

copy_local_file(source: Union[pathlib.Path, str], dest: Union[pathlib.Path, str]) → None
 Copy the contents of a local file to a destination in swift

property default_container

delete_file(path: Union[pathlib.Path, str], dry_run: bool = False) → int
 Delete the provided path, recursively if necessary.

property directory

exists(path: Union[pathlib.Path, str]) → bool
 Check whether the provided path exists

find(root: Union[pathlib.Path, str], dirs: bool = True) → str
 A test helper simulating ‘find’.
 Iterates over directories and filenames, given as relative paths to the root.

get_config_value(config_key: str, *env_keys: Any, default: Optional[str] = None) → Optional[str]

get_container(container: Optional[str] = None) → List[Dict[str, str]]
 Given the name of a container, return its contents.

Parameters **container** (*str*) – The name of the desired container, defaults to *default_container*

Returns A list of objects in the container if it exists

Return type List[Dict[str, str]]

Example:

```
>>> plugin.get_container("bandersnatch")
[ {
    'bytes': 1101, 'last_modified': '2020-02-27T19:10:17.922970',
    'hash': 'a76b4c69bfcf82313bbdc0393b04438a',
    'name': 'packages/pyyaml/PyYAML-5.3/LICENSE',
    'content_type': 'application/octet-stream'
}, {
    'bytes': 1779, 'last_modified': '2020-02-27T19:10:17.845520',
    'hash': 'c60081e1ad65830b098a7f21a8a8c90e',
    'name': 'packages/pyyaml/PyYAML-5.3/PKG-INFO',
    'content_type': 'application/octet-stream'
}, {
    'bytes': 1548, 'last_modified': '2020-02-27T19:10:17.730490',
    'hash': '9a8bdf19e93d4b007598b5eb97b461eb',
    'name': 'packages/pyyaml/PyYAML-5.3/README',
    'content_type': 'application/octet-stream'
}, ...
]
```

get_hash (*path*: Union[pathlib.Path, str], *function*: str = 'sha256') → str

Get the sha256sum of a given **path**

get_lock (*path*: Optional[str] = None) → bandersnatch_storage_plugins.swift.SwiftFileLock

Retrieve the appropriate *FileLock* backend for this storage plugin

Parameters **path** (str) – The path to use for locking

Returns A *FileLock* backend for obtaining locks

Return type SwiftFileLock

get_object (*container_name*: str, *file_path*: str) → bytes

Retrieve an object from swift, base64 decoding the contents.

initialize_plugin() → None

Code to initialize the plugin

is_dir (*path*: Union[pathlib.Path, str]) → bool

Check whether the provided path is a directory.

is_file (*path*: Union[pathlib.Path, str]) → bool

Check whether the provided path is a file.

is_symlink (*path*: Union[pathlib.Path, str]) → bool

Check whether the provided path is a symlink

mkdir (*path*: Union[pathlib.Path, str], *exist_ok*: bool = False, *parents*: bool = False) → None

Create the provided directory

This operation is a no-op on swift.

name = 'swift'

open_file (*path*: Union[pathlib.Path, str], *text*: bool = True) → Generator[IO, None, None]

Yield a file context to iterate over. If text is false, open the file with 'rb' mode specified.

read_file (*path*: Union[pathlib.Path, str], *text*: bool = True, *encoding*: str = 'utf-8', *errors*: Optional[str] = None) → Union[str, bytes]

Return the contents of the requested file, either a a bytestring or a unicode string depending on whether **text** is True

rewrite (*filepath*: Union[pathlib.Path, str], *mode*: str = 'w', **kw: Any) → Generator[IO, None, None]
Rewrite an existing file atomically to avoid programs running in parallel to have race conditions while reading.

rmdir (*path*: Union[pathlib.Path, str], *recurse*: bool = False, *force*: bool = False, *ignore_errors*: bool = False, *dry_run*: bool = False) → int
Remove the directory. If recurse is True, allow removing empty children.
If force is true, remove contents destructively.

symlink (*src*: Union[pathlib.Path, str], *dest*: Union[pathlib.Path, str], *src_container*: Optional[str] = None, *src_account*: Optional[str] = None) → None
Create a symlink at **dest** that points back at **source**

update_safe (*filename*: Union[pathlib.Path, str], **kw: Any) → Generator[IO, None, None]
Rewrite a file atomically.
Clients are allowed to delete the tmpfile to signal that they don't want to have it updated.

update_timestamp (*path*: Union[pathlib.Path, str]) → None

walk (*root*: Union[pathlib.Path, str], *dirs*: bool = True, *conn*: Optional[swiftclient.client.Connection] = None) → List[bandersnatch_storage_plugins.swift.SwiftPath]

write_file (*path*: Union[pathlib.Path, str], *contents*: Union[str, bytes, IO], *encoding*: Optional[str] = None, *errors*: Optional[str] = None) → None
Write data to the provided path. If **contents** is a string, the file will be opened and written in "r" + "utf-8" mode, if bytes are supplied it will be accessed using "rb" mode (i.e. binary write).

PYTHON MODULE INDEX

b

bandersnatch, 19
bandersnatch.configuration, 19
bandersnatch.delete, 20
bandersnatch.filter, 20
bandersnatch.log, 22
bandersnatch.main, 22
bandersnatch.master, 22
bandersnatch.mirror, 23
bandersnatch.package, 24
bandersnatch.storage, 25
bandersnatch.utils, 27
bandersnatch.verify, 28
bandersnatch_filter_plugins, 28
bandersnatch_filter_plugins.blacklist_name,
 28
bandersnatch_filter_plugins.filename_name,
 29
bandersnatch_filter_plugins.latest_name,
 29
bandersnatch_filter_plugins.metadata_filter,
 30
bandersnatch_filter_plugins.prerelease_name,
 32
bandersnatch_filter_plugins.regex_name,
 33
bandersnatch_filter_plugins.whitelist_name,
 33
bandersnatch_storage_plugins, 34
bandersnatch_storage_plugins.filesystem,
 34
bandersnatch_storage_plugins.swift, 36

INDEX

A

absolute() (bandersnatch.storage_plugins.swift.SwiftPath method), 36
all_packages() (bandersnatch.master.Master method), 22
allowlist_package_names (bandersnatch.filter_plugins.whitelist_name.AllowlistRelease attribute), 33
AllowlistRelease (class in bandersnatch.filter_plugins.whitelist_name), 33
async_main() (in module bandersnatch.main), 22

B

BACKEND (bandersnatch_storage_plugins.swift.SwiftPath attribute), 36
backend() (bandersnatch_storage_plugins.swift.SwiftPath property), 36
bandersnatch module, 19
bandersnatch.configuration module, 19
bandersnatch.delete module, 20
bandersnatch.filter module, 20
bandersnatch.log module, 22
bandersnatch.main module, 22
bandersnatch.master module, 22
bandersnatch.mirror module, 23
bandersnatch.package module, 24
bandersnatch.storage module, 25
bandersnatch.utils module, 27
bandersnatch.verify module, 28

bandersnatch_filter_plugins module, 28
bandersnatch_filter_plugins.blacklist_name module, 28
bandersnatch_filter_plugins.filename_name module, 29
bandersnatch_filter_plugins.latest_name module, 29
bandersnatch_filter_plugins.metadata_filter module, 30
bandersnatch_filter_plugins.prerelease_name module, 32
bandersnatch_filter_plugins.regex_name module, 33
bandersnatch_filter_plugins.whitelist_name module, 33
bandersnatch_safe_name() (in module bandersnatch.utils), 27
bandersnatch_storage_plugins module, 34
bandersnatch_storage_plugins.filesystem module, 34
bandersnatch_storage_plugins.swift module, 36
BandersnatchConfig (class in bandersnatch.configuration), 19
blacklist_package_names (bandersnatch.filter_plugins.blacklist_name.BlacklistProject attribute), 28
blacklist_package_names (bandersnatch.filter_plugins.blacklist_name.BlacklistRelease attribute), 29
BlacklistProject (class in bandersnatch.filter_plugins.blacklist_name), 28
BlacklistRelease (class in bandersnatch.filter_plugins.blacklist_name), 29

C

canonicalize_package() (bandersnatch.storage.Storage static method), 25
changed_packages() (bandersnatch.master.Master method), 22

check_for_stale_cache() (bander-
snatch.master.Master method), 22
check_match() (bandersnatch.filter.Filter method),
20
check_match() (bander-
snatch_filter_plugins.blacklist_name.BlacklistProject
method), 28
check_match() (bander-
snatch_filter_plugins.regex_name.RegexProjectFilter
method), 33
check_match() (bander-
snatch_filter_plugins.whitelist_name.WhitelistProject
method), 34
cleanup() (bandersnatch.configuration.SetConfigValues
property), 19
cleanup_non_pep_503_paths() (bander-
snatch.mirror.Mirror method), 23
compare_files() (bandersnatch.storage.Storage
method), 25
compare_files() (bander-
snatch_storage_plugins.filesystem.FilesystemStorage
method), 34
compare_files() (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 37
connection() (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 37
convert_url_to_path() (in module bander-
snatch.utils), 27
copy_file() (bandersnatch.storage.Storage method),
25
copy_file() (bander-
snatch_storage_plugins.filesystem.FilesystemStorage
method), 34
copy_file() (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 37
copy_local_file() (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 37

D

default_container() (bander-
snatch_storage_plugins.swift.SwiftStorage
property), 37
delete() (bandersnatch.storage.Storage method), 25
delete_file() (bandersnatch.storage.Storage
method), 25
delete_file() (bander-
snatch_storage_plugins.filesystem.FilesystemStorage
method), 34
delete_file() (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 37

E

ENTRYPOINT_GROUPS (bander-
snatch.filter.LoadedFilters attribute), 21
errors (bandersnatch.mirror.Mirror attribute), 23
ExcludePlatformFilter (class in bander-
snatch_filter_plugins.filename_name), 29
exists() (bandersnatch.storage.Storage method), 25
exists() (bandersnatch_storage_plugins.filesystem.FilesystemStorage
method), 34
exists() (bandersnatch_storage_plugins.swift.SwiftPath
method), 36
exists() (bandersnatch_storage_plugins.swift.SwiftStorage
method), 37

F

FilesystemStorage (class in bander-
snatch_storage_plugins.filesystem), 34

Filter (class in `bandersnatch.filter`), 20
`filter()` (`bandersnatch.filter.Filter` method), 20
`filter()` (`bandersnatch_filter_plugins.blacklist_name.BlacklistProject`
 method), 29
`filter()` (`bandersnatch_filter_plugins.blacklist_name.BlacklistRelease`
 method), 29
`filter()` (`bandersnatch_filter_plugins.filename_name.ExcludePlatformFilter`
 method), 29
`filter()` (`bandersnatch_filter_plugins.latest_name.LatestReleaseFilter`
 method), 29
`filter()` (`bandersnatch_filter_plugins.metadata_filter.RegexFilter`
 method), 30
`filter()` (`bandersnatch_filter_plugins.metadata_filter.RegexProjectMetadataFilter`
 method), 30
`filter()` (`bandersnatch_filter_plugins.metadata_filter.RegexReleaseFileMetadataFilter`
 method), 31
`filter()` (`bandersnatch_filter_plugins.metadata_filter.VersionRangeFilter`
 method), 31
`filter()` (`bandersnatch_filter_plugins.metadata_filter.VersionRangeReleaseFileMetadataFilter`
 method), 32
`filter()` (`bandersnatch_filter_plugins.prerelease_name.PreReleaseFilter`
 method), 32
`filter()` (`bandersnatch_filter_plugins.regex_name.RegexProjectFilter`
 method), 33
`filter()` (`bandersnatch_filter_plugins.regex_name.RegexReleaseFilter`
 method), 33
`filter()` (`bandersnatch_filter_plugins.whitelist_name.AllowlistRelease`
 method), 33
`filter()` (`bandersnatch_filter_plugins.whitelist_name.WhitelistProject`
 method), 34
`filter_metadata_plugins()` (bander-
 snatch.filter.LoadedFilters method), 21
`filter_project_plugins()` (bander-
 snatch.filter.LoadedFilters method), 21
`filter_release_file_plugins()` (bander-
 snatch.filter.LoadedFilters method), 21
`filter_release_plugins()` (bander-
 snatch.filter.LoadedFilters method), 21
`FilterMetadataPlugin` (class in bander-
 snatch.filter), 20
`FilterProjectPlugin` (class in bander-
 snatch.filter), 21
`FilterReleaseFilePlugin` (class in bander-
 snatch.filter), 21
`FilterReleasePlugin` (class in bander-
 snatch.filter), 21
`find()` (`bandersnatch.storage.Storage` method), 25
`find()` (`bandersnatch_storage_plugins.filesystem.FilesystemStorage`
 method), 34
`find()` (`bandersnatch_storage_plugins.swift.SwiftStorage`
 method), 37
`find()` (in module `bandersnatch.utils`), 27
`find_package_indexes_in_dir()` (bander-
 snatch.mirror.Mirror method), 23
G
`get_date_requires_python()` (bander-
 snatch.package.Package method), 24
`get_platform_page()` (bander-
 snatch.package.Package method), 24
`get_release_file()` (bandersnatch.mirror.Mirror
 property), 23
`get_config_value()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 37
`get_containing()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 37
`get_flock_path()` (bandersnatch.storage.Storage
 method), 31
`get_hash()` (bandersnatch.storage.Storage method),
`get_hash()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 35
`get_hashes()` (bander-
 storage_plugins.filesystem.FilesystemStorage
 method), 35
`get_json_paths()` (bandersnatch.storage.Storage
 method), 25
`get_latest_json()` (in module bander-
 snatch.verify), 28
`get_lock()` (bandersnatch.storage.Storage method),
 25
`get_lock()` (bander-
 storage_plugins.filesystem.FilesystemStorage
 method), 35
`get_lock()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 38
`get_object()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 38
`get_package_metadata()` (bander-
 storage_plugins.swift.SwiftStorage
 method), 22
`get_simple_dirs()` (bandersnatch.mirror.Mirror
 method), 23
H
`hash()` (in module `bandersnatch.utils`), 27
`hash_file()` (bandersnatch.storage.Storage method),
 25
I
`info()` (bandersnatch.package.Package property), 24

K

`keep(bandersnatch_filter_plugins.latest_name.LatestReleaseFilter attribute), 29`

L

`last_serial() (bandersnatch.package.Package property), 24`
`latest(bandersnatch_filter_plugins.latest_name.LatestReleaseFilter attribute), 30`
`LatestReleaseFilter (class in bandersnatch_filter_plugins.latest_name), 29`
`load_configuration() (bandersnatch.configuration.BandersnatchConfig method), 19`
`load_storage_plugins() (in module bandersnatch.storage), 26`
`LoadedFilters (class in bandersnatch.filter), 21`

M

`main() (in module bandersnatch.main), 22`
`make_time_stamp() (in module bandersnatch.utils), 27`
`Master (class in bandersnatch.master), 22`
`match_patterns (bandersnatch_filter_plugins.metadata_filter.RegexFilter attribute), 30`
`match_patterns (bandersnatch_filter_plugins.metadata_filter.RegexProjectFilter attribute), 30`
`match_patterns (bandersnatch_filter_plugins.metadata_filter.RegexReleaseFileFilter attribute), 31`
`metadata() (bandersnatch.package.Package property), 24`
`metadata_verify() (in module bandersnatch.verify), 28`
`Mirror (class in bandersnatch.mirror), 23`
`mirror() (in module bandersnatch.mirror), 24`
`mkdir() (bandersnatch.storage.Storage method), 25`
`mkdir() (bandersnatch_storage_plugins.filesystem.Filesystem method), 35`
`mkdir() (bandersnatch_storage_plugins.swift.SwiftPath method), 36`
`mkdir() (bandersnatch_storage_plugins.swift.SwiftStorage method), 38`
`module`
 `bandersnatch, 19`
 `bandersnatch.configuration, 19`
 `bandersnatch.delete, 20`
 `bandersnatch.filter, 20`
 `bandersnatch.log, 22`
 `bandersnatch.main, 22`
 `bandersnatch.master, 22`
 `bandersnatch.mirror, 23`

`bandersnatch.package, 24`
`bandersnatch.storage, 25`
`bandersnatch.utils, 27`
`bandersnatch.verify, 28`
`bandersnatch_filter_plugins, 28`
`bandersnatch_filter_plugins.blacklist_name, 28`
`bandersnatch_filter_plugins.filename_name, 29`
`bandersnatch_filter_plugins.latest_name, 29`
`bandersnatch_filter_plugins.metadata_filter, 30`
`bandersnatch_filter_plugins.prerelease_name, 32`
`bandersnatch_filter_plugins.regex_name, 33`
`bandersnatch_filter_plugins.whitelist_name, 33`
`bandersnatch_storage_plugins, 34`
`bandersnatch_storage_plugins.filesystem, 34`
`bandersnatch_storage_plugins.swift, 36`

N

`name (bandersnatch.filter.Filter attribute), 20`
`Name (bandersnatch.filter.FilterMetadataPlugin attribute), 20`
`name (bandersnatch.filter.FilterProjectPlugin attribute), 21`
`name (bandersnatch.filter.FilterReleaseFilePlugin attribute), 21`
`name (bandersnatch.filter.FilterReleasePlugin attribute), 21`
`name (bandersnatch.storage.Storage attribute), 26`
`name (bandersnatch.storage.StoragePlugin attribute), 26`
`name (bandersnatch_filter_plugins.blacklist_name.BlacklistProject attribute), 29`
`name (bandersnatch_filter_plugins.blacklist_name.BlacklistRelease attribute), 29`
`name (bandersnatch_filter_plugins.filename_name.ExcludePlatformFilter attribute), 29`
`name (bandersnatch_filter_plugins.latest_name.LatestReleaseFilter attribute), 30`
`name (bandersnatch_filter_plugins.metadata_filter.RegexFilter attribute), 30`
`name (bandersnatch_filter_plugins.metadata_filter.RegexProjectMetadataFilter attribute), 30`
`name (bandersnatch_filter_plugins.metadata_filter.RegexReleaseFileMetadataFilter attribute), 31`
`name (bandersnatch_filter_plugins.metadata_filter.VersionRangeFilter attribute), 31`

name (*bandersnatch_filter_plugins.metadata_filter.VersionRangeProjectMetadataFilter* attribute), 31
name (*bandersnatch_filter_plugins.metadata_filter.VersionRangeReleaseFileMetadataFilter* attribute), 32
name (*bandersnatch_filter_plugins.prerelease_name.PreReleaseFilter*)
name (*bandersnatch_filter_plugins.regex_name.RegexProjectFilter* attribute), 33
name (*bandersnatch_filter_plugins.regex_name.RegexReleaseFilter* attribute), 33
name (*bandersnatch_filter_plugins.whitelist_name.AllowlistRelease* method), 32
name (*bandersnatch_filter_plugins.whitelist_name.WhitelistProject* attribute), 34
name (*bandersnatch_storage_plugins.filesystem.FilesystemStorage* attribute), 35
name (*bandersnatch_storage_plugins.swift.SwiftStorage* attribute), 38
need_index_sync (*bandersnatch.mirror.Mirror* attribute), 23
new_key () (*bandersnatch.configuration.DeprecatedKey* property), 19
new_section () (*bandersnatch.configuration.DeprecatedKey* property), 19
now (*bandersnatch.mirror.Mirror* attribute), 23
nulls_match (*bandersnatch_filter_plugins.metadata_filter.RegexFilter* attribute), 30
nulls_match (*bandersnatch_filter_plugins.metadata_filter.RegexProjectMetadataFilter* attribute), 30
nulls_match (*bandersnatch_filter_plugins.metadata_filter.RegexReleaseFileMetadataFilter* attribute), 30
nulls_match (*bandersnatch_filter_plugins.metadata_filter.RegexReleaseFilter* attribute), 31
nulls_match (*bandersnatch_filter_plugins.metadata_filter.VersionRangeFilter* attribute), 31
nulls_match (*bandersnatch_filter_plugins.metadata_filter.VersionRangeProjectMetadataFilter* attribute), 31
nulls_match (*bandersnatch_filter_plugins.metadata_filter.VersionRangeReleaseFileMetadataFilter* attribute), 32

O

old_key () (*bandersnatch.configuration.DeprecatedKey* property), 19
old_section () (*bandersnatch.configuration.DeprecatedKey* property), 19
open_file () (*bandersnatch.storage.Storage* method), 26

P

Package (class in *bandersnatch.package*), 24
package_syncer () (*bandersnatch.mirror.Mirror* method), 23
PackageNotFound, 22
Packages_to_sync (*bandersnatch.mirror.Mirror* attribute), 23

R

read_bytes () (*bandersnatch_storage_plugins.swift.SwiftPath* method), 36
read_file () (*bandersnatch.storage.Storage* method), 26
read_file () (*bandersnatch_storage_plugins.filesystem.FilesystemStorage* method), 35

```

read_file() (bander- specifiers (bander-
snatch_storage_plugins.swift.SwiftStorage
method), 38
read_text() (bander- specifiers (bander-
snatch_storage_plugins.swift.SwiftPath
method), 36
record_finished_package() (bander- specifiers (bander-
snatch.mirror.Mirror method), 23
recursive_find_files() (in module bander- specifiers (bander-
snatch.utils), 27
RegexFilter (class in bander- specifiers (bander-
snatch_filter_plugins.metadata_filter), 30
RegexProjectFilter (class in bander- specifiers (bander-
snatch_filter_plugins.regex_name), 33
RegexProjectMetadataFilter (class in bander- specifiers (bander-
snatch_filter_plugins.metadata_filter), 30
RegexReleaseFileMetadataFilter (class in bander- specifiers (bander-
bandersnatch_filter_plugins.metadata_filter),
30
RegexReleaseFilter (class in bander- specifiers (bander-
snatch_filter_plugins.regex_name), 33
register_backend() (bander- specifiers (bander-
snatch_storage_plugins.swift.SwiftPath class
method), 36
release_files() (bandersnatch.package.Package
property), 24
releases() (bandersnatch.package.Package prop-
erty), 24
rewrite() (bandersnatch.storage.Storage method), 26
rewrite() (bandersnatch_storage_plugins.filesystem.Filesystem
method), 35
rewrite() (bandersnatch_storage_plugins.swift.SwiftStorage
method), 38
rewrite() (in module bandersnatch.utils), 27
rmdir() (bandersnatch.storage.Storage method), 26
rmdir() (bandersnatch_storage_plugins.filesystem.Filesystem
method), 35
rmdir() (bandersnatch_storage_plugins.swift.SwiftStorage
method), 39
root_uri (bandersnatch.mirror.Mirror attribute), 23
root_uri() (bander- sync() (bandersnatch.package.Package method), 24
snatch.configuration.SetConfigValues prop-
erty), 20
sync_to() (bander- sync_to_index_page() (bandersnatch.mirror.Mirror
method), 36
method), 39
sync_packages() (bandersnatch.mirror.Mirror
method), 23
sync_release_files() (bander-
snatch.package.Package method), 24
sync_simple_page() (bander-
snatch.package.Package method), 24
synced_serial (bandersnatch.mirror.Mirror at-
tribute), 23
synchronize() (bandersnatch.mirror.Mirror
method), 23
target_serial (bandersnatch.mirror.Mirror at-
tribute), 24
todolist() (bandersnatch.mirror.Mirror property),
24
Singleton (class in bandersnatch.configuration), 20

```

S

save_json_metadata() (bander-
snatch.package.Package method), 24
SetConfigValues (class in bander-
snatch.configuration), 19
setup_logging() (in module bandersnatch.log), 22
simple_directory() (bander-
snatch.package.Package property), 24
Singleton (class in bandersnatch.configuration), 20

T

target_serial (bandersnatch.mirror.Mirror at-
tribute), 24
todolist() (bandersnatch.mirror.Mirror property),
24

touch() (*bandersnatch_storage_plugins.swift.SwiftPath* write_bytes() (bandersnatch method), 36
unlink() (*bandersnatch_storage_plugins.swift.SwiftPath* write_file() (bandersnatch.storage.Storage method), 26
unlink_parent_dir() (in module bandersnatch.utils) write_file() (bandersnatch_storage_plugins.filesystem.FilesystemStorage method), 35
update_metadata() (bandersnatch.package.Package method), 24
update_safe() (bandersnatch.storage.Storage method), 26 write_file() (bandersnatch_storage_plugins.swift.SwiftStorage method), 39
update_safe() (bandersnatch_storage_plugins.filesystem.FilesystemStorage method), 35 write_text() (bandersnatch_storage_plugins.swift.SwiftPath method), 37
update_safe() (bandersnatch_storage_plugins.swift.SwiftStorage method), 39
update_timestamp() (bandersnatch_storage_plugins.swift.SwiftStorage method), 39
url_fetch() (bandersnatch.master.Master method), 22
user_agent() (in module bandersnatch.utils), 27

V

validate_config_values() (in module bandersnatch.configuration), 20
verify() (in module bandersnatch.verify), 28
verify_producer() (in module bandersnatch.verify), 28
VersionRangeFilter (class in bandersnatch_filter_plugins.metadata_filter), 31
VersionRangeProjectMetadataFilter (class in bandersnatch_filter_plugins.metadata_filter), 31
VersionRangeReleaseFileMetadataFilter (class in bandersnatch_filter_plugins.metadata_filter), 32

W

walk() (bandersnatch_storage_plugins.filesystem.FilesystemStorage method), 35
walk() (bandersnatch_storage_plugins.swift.SwiftStorage method), 39
webdir() (bandersnatch.mirror.Mirror property), 24
whitelist_package_names (bandersnatch_filter_plugins.whitelist_name.WhitelistProject attribute), 34
WhitelistProject (class in bandersnatch_filter_plugins.whitelist_name), 34
wrapup_successful_sync() (bandersnatch.mirror.Mirror method), 24

X

xmlrpc_url() (bandersnatch.master.Master property), 22
XmlRpcError, 22